

CANON MK5000 SPECIFICATION



Specification	Details
Printing Method	Thermal Transfer
Printing Resolution	300 dpi
Printing Speed (Tube)	High: 40 mm/s Middle: 25 mm/s Low: 18.5 mm/s
Output Rate (approx.)	High: 55 pcs/min (ø1.5 – 6.5mm), 45 pcs/min (ø7 – 10mm) Middle: 35 pcs/min Low: 30 pcs/min
Ink Ribbon	Black: 150m / Black: 40m / White: 85m
Cut Length	Tube: 8 - 150mm Label Tape/Plate: 4 - 150mm
Character Size	1.3mm (only full-width) 2mm, 2.6mm, 3mm, 4mm, 6mm (half-width/full-width)
Number of Lines	Up to 3 lines
Input Mode	Alphanumeric, Symbol Input
Display	LCD (160 x 64 dots), backlight 10 characters/line × 2 lines (full-width)
Built-in Memory	Print Data: 5,000 characters File Storage: 25,000 characters, up to 10 folders
Media Cutting Method	Automatic Full-Cut, Automatic Half-Cut
Power Supply	AC Adaptor (100 - 240V, 50/60Hz, 0.74A)
Rechargeable Batteries	Panasonic eneloop AA (BK-3MCCE) × 6 pieces
Power Consumption	Maximum 25W

Specification	Details
Interface	USB2.0 Full-Speed (USB1.1 compatible)
Operating Temp.	15 – 32.5°C (5 – 18°C with optional tube warmer)
Operating Humidity	10 – 85% RH (no condensation)
Storage Temp.	5 – 35°C
Storage Humidity	10 – 90% RH (no condensation)
Dimensions (W×D×H)	272 × 318 × 97mm
Weight	Approx. 2.7 kg (without accessories)
Print Media	<p>PVC/Clear Tube: ø1.5 - 10mm, ø1.5 - 6.5mm (with warmer), 0.4 - 0.6mm thickness</p> <p>Heat Shrink Tube: ø1.5 - 10mm, 0.2 - 0.4mm thickness</p> <p>Label Tape: Widths - 6mm, 9mm, 12mm; Lengths - 30m (White/Yellow), 27m (Silver)</p> <p>Flat Tube: ø1.5 - 6.5mm; Width ≤ 11.2mm; Thickness: 0.4 - 0.6mm</p> <p>Plate: Width 8 - 10mm; Thickness: 0.5mm</p>

Canon

Delighting You Always

